

## HEATING OIL:

# Gas Oil

With an ultra low sulphur content, Gas Oil Heating Oil is an environmental improvement in the manufacture of traditional fuel oils.

Developed and manufactured specifically as a clean burning heating oil, Ultra35 is the heating oil of choice for the commercial environment.

Manufactured to BS 2869, the British Approved Standard for heating oil, Ultra35 Heating Oil is ideal for applications such as hotels and large public buildings which rely on significant quantities of heating oil.

Ultra35 Heating Oil is a specialist heating oil and is not designed for Diesel Engines.

### Benefits

- Clean burning fuel with reduced carbon content
- Reduced CO2 output per KW/H
- Renewable/ recycled content
- High Smoke point & low char value

### Availability

Gas Oil Heating Oil is available from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



### Specifications

BS 2869 Parameters

Test description	Specifications
Appearance	Clear and Bright
Odour	Merchantable
Density at 15 °C	0.82 - 0.85 kg/litre
Kinematics Viscosity	2.4 -4.5 max
Cold Filter Plugging Point	-24 °C
Flash Point	55 °C
Sulphur %	0.0- 0.1 wt
Ash %	0.001 max
Sediment %	0.001 max
Copper Corrosion Test	Class 1
Water %	0.001 max
Acid Number	Nil
Residue	180Micron

Product is marked (HMRC Statutory Marker)

Calorific Value	KJ's per Litre
Gas Oil	38,000
Kerosene	35,000



**martindale**  
Fuels



**CPL** PETROLEUM

### Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com