

## ROAD FUEL:

# Diesel

A standard diesel product manufactured to EN590.  
Suitable for all standard diesel applications.

Delivering maximum energy release per litre and better performance through cold months combined with lubricative qualities; Diesel is well suited to most on-the-road vehicles. For use with all road-diesel powered vehicles including lorries, cars and vans.

### Benefits

- Manufactured to BS EN 590
- Suitable for all diesel vehicles
- Competitive pricing for standard product

### Availability

Standard diesel is available for use with all road-diesel powered vehicles from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



### Specifications

BS EN 590 Parameters

Test description	Specifications
Appearance	Clear and Bright
Colour	2.5 max
Odour	Merchantable
Density at 15 °C	845 kg/m <sup>3</sup> max
Viscosity at 40 °C	24.5 cSt max
Flash Point	56 °C min
Cold Plugging Point - Winter	-15 °C max
Cold Plugging Point -Summer	5°Cmax
Cloud Point - Winter	-5 °C
Cloud Point - Summer	3 °C
Cetane Number	51 min
Cetane Index	46 min
Ash Content %	0.01 wt max
Water Content %	200 mg/kg max
Sulphur %	10 mg/kh max
Copper Corrosion (3 hrs, 50 °C)	1 max
Carbon Residue (10% bottoms)	0.30wt max
Particulate Matter	24 mg/kg

**Carlton**  
FUELS

**m**

**martindale**  
Fuels

**Emo**

**CPL** PETROLEUM

### Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com