

HEATING OIL:



Developed to compliment ESL Fuels' biodiesel range, GreenFlame is the UK's first part-renewable/recycled heating oil.

Manufactured using renewable/recycled oils as well as traditional crude oils, and with a viscosity of 35 sec, GreenFlame is a direct alternative to traditional petroleum based heating oil for the commercial environment.

With its renewable/recycled content and ultra low sulphur credentials, GreenFlame is a step in the right direction towards reducing emissions and the UK's dependence on fossil fuels.

Fully compliant to BS 2869, the British Approved Standard for heating oil, GreenFlame offers enormous commercial opportunities in applications such as factories, hotels and large public buildings which rely on significant quantities of traditional gasoil and where it can be used without modification in existing boiler systems.

- GreenFlame is produced in bulk at ESL Biofuels' Cheshire plant and is available nationwide through some of the country's leading fuel distributors.

Availability

GreenFlame is available from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



Specifications

BS 2869 Parameters

Test description	Specifications
Appearance	Clear & Bright
Odour	Merchantable
Density at 15 °C	0.82 - 0.85 kg/litre max
Kinematic Viscosity	2.40 - 4.5 cSt max
Cold Filter Plugging Point	-24°C
Flash Point	55 °C min
Sulphur %	0.0 - 0.1 m/m max
Sediment %	0.001 m/m max
Water Content %	0.001 v/v max
Ash Content %	0.001 m/m max
Copper Corrosion Test	Class 1
Lubricity	180 Micron
Strong Acid Number	zero

Product is marked (HMRC Statutory Marker)

Calorific Value	KJ's per Litre
Gas Oil	38,000
Kerosene	35,000
Ultra35 Heating Oil	38,000



martindale
Fuels



CPL PETROLEUM

Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com