

FUEL OIL:

Light

LFO is an easy to use, low viscosity fuel oil for industrial application.

Our Light Fuel Oil is blended with good quality fuel oil and is formulated for use in small-scale industrial heating processes (boilers and other combustion equipment) where fuel oil is required but ease of use is an important factor.

Benefits

- Clean burning fuel with low viscosity.
- Low pour point (-25c)

Availability

Light Fuel Oil is available from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



Specifications

BS 2869 Parameters

Test description	Specifications
Density at 15°C	935 kg/m ³
Viscosity at 100°C	8.2 mm ² /s ² max
Flash Point	66 °C min
Sulphur %	1.0 m/m
Water Content %	0.5 v/v max
Ash Content %	0.1 m/m max
Carbon Residue (micro) %	15 m/m max
Pour point	25 °C
Total Sediment (existent) %	0.1 m/m max
Strong Acid Number	zero
Gross Calorific Value	42.5 MJ/L

Carlton
FUELS

m

martindale
Fuels

Emo

CPL PETROLEUM

Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com