

## FUEL OIL:

# Medium

MFO is an easy to use, blend of various oils for heavier industrial application.

A balance of distillate and heavier fuel oils; Medium Fuel Oil is a standard fuel blended for use in many industrial operations.

### Benefits

- Manufactured using streams from local refiners
- Meets BS 2869:2006
- Suits a wide range of boiler applications

### Availability

Medium Fuel Oil is available from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



### Specifications

BS 2869 Parameters

Test description	Specifications
Density at 15 °C	935 kg/m <sup>3</sup>
Viscosity at 100°C	8.2 - 20 mm <sup>2</sup> /s <sup>a</sup>
Flash Point	66 °C min
Sulphur %	1.0 m/m
Water Content %	0.75 v/v max
Ash Content %	0.1 m/m max
Carbon Residue (micro) %	18 m/m max
Pour point	20 °C
Total Sediment (existent) %	0.15 m/m max
Strong Acid Number	zero
Gross Calorific Value	41.3 MJ/L

**Carlton**  
FUELS



**martindale**  
Fuels



**CPL** PETROLEUM

### Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: [info@eslfuels.com](mailto:info@eslfuels.com) [www.eslfuels.com](http://www.eslfuels.com)