

MARINE FUEL:

IFO380

A standard low sulphur 380cst fuel. Sulphur Emission Control Area (SECA) compliant at 1.5% sulphur max. All components are sourced from local refiners, producing a quality, low risk fuel.

Low sulphur 380cst fuel is available and even heavier marine fuels can be manufactured and supplied on request.

Benefits

- Low sulphur fuel
- All blend components sourced from local refiners
- Easily meets ISO 8217 specifications

Availability

Marine IFO380 is available directly from ESL Fuels and also via some of the leading fuel distributors in the North West.



Specifications

ISO 8217 Parameters

Test description	Specifications
Density at 15 °C	991 kg/m ³ max
Viscosity at 50 °C	380 mm ² /s max
Flash Point	60 °C min
Pour Point - Winter	30 °C max
Carbon Residue %	18 m/m max
Ash Content %	0.15 m/m max
Water Content %	0.5 m/m max
Sulphur %	1.5 m/m max
Vanadium	300 mg/kg
Total Sediment potential %	0.10 m/m max
Aluminium plus silicon	80 mg/kg
Zinc ppm	15 max
Phosphorus ppm	15 max
Calcium ppm	30 mg/kg

Carlton
FUELS

m

martindale
Fuels

Emo

CPL PETROLEUM

Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com