

ROAD FUEL:

Ultra²⁰

Manufactured as a diesel blend using renewable plant oils as well as traditional crude oils, and oxygenated during the blending process to create a cleaner burning fuel, Ultra20 is our latest biodiesel product.

A commercial alternative to conventional petroleum diesel fuel, Ultra20 offers the same appearance, performance and fuel economy and is comparable in price. However, with an ultra low sulphur content, Ultra20 releases up to 20% lower CO2 and dramatically reduces a vehicle's harmful emissions.

Ultra20 complies with EN 590, the European Standard for diesel, and is suitable for both traditional and modern common rail diesel engines. The biodiesel is already fully approved by many of the leading commercial vehicle and engine manufacturers including Cummins, Citroen, Peugeot and Daimler-Chrysler, however we would always recommend checking warranty arrangements with specific manufacturers before use.

Availability

Ultra20 is available for use with all road-diesel powered vehicles from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



Specifications

BS EN 590 Parameters

Test description	Typical Spec
Odour	Merchantable
Density at 15 °C	0.845 kg/litre
Kinematics Viscosity	3.5
Flash Point	60 °C
Cold Filter Plugging Point	-24°C
Cetane Number	58
Ash Content %	0.001
Sediment %	0.001
Water Content %	0.001
Sulphur %	0.0-0.1
Copper Corrosion Test	Class 1
Acid Number	Nil
Lubricity	180 Micron



martindale
Fuels



CPL PETROLEUM

Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com