

HEATING OIL:

Ultra^{LHO}

Ultra LHO is an easy to use, low viscosity fuel oil for industrial application.

Manufactured to BS 2869, the British Approved Standard for heating oil, Ultra^{LHO} is ideal for applications such as quarrying, heavy manufacturing and other industrial applications which rely on significant quantities of heating oil.

Benefits

- Clean burning fuel with very low viscosity.
- Low pour point (-20c)
- High quality virgin fuel

Availability

Ultra^{LHO} is available from some of the leading fuel distributors in the North West. To request a quote, please contact 0800 33 99 77.



Specifications

BS 2869 Parameters

Test description	Specifications
Appearance	Dark and clear
Odour	Merchantable
Density at 15 °C	-0.86 kg/litre
Kinematic Viscosity	3.5 - 6 cSt max
Cold Filter Plugging Point	-15°C
Flash Point	55 °C min
Sulphur %	1.0 m/m max
Sediment %	0.005 m/m max
Water Content %	0.005 v/v max
Ash Content %	0.005 m/m max
Copper Corrosion Test	Class 1
Lubricity	180 Micron
Acid Number	zero

Carlton
FUELS



martindale
Fuels

Emo

CPL PETROLEUM

Ebony Solutions Ltd

Wincham Lane, Wincham, Northwich, Cheshire CW9 6DE

T: 01606 301 222 F: 01606 872 666

E: info@eslfuels.com www.eslfuels.com